Environment Clearance Compliance Report (October 2019- March 2020)

for

'Granite Building Stone Quarry of Mr. C.G.GEORGE.' E.C.No:155/KNR/2017/DEIAA, Dated:5.01.2018

Extent: 0.7682 Ha. (1.8982 Acres)

At

Sy No. : 73/4,79,80/1C,81/1 & 81/2

Village : Patiam
Taluk : Thalassery
District : Kannur
State : Kerala

Compliance Status of the General Conditions for Mining Projects Laid down by the State Environment Impact Assessment Authority, Kerala vide their Environment Clearance No.81/2017 dated 05/01/2018.

SPECIFIC CONDITIONS

Sl.No	Condition	Status of Compliance
1	A Mines Manager shall be appointed to control, direct, manage and supervise Quarrying Operations as required under the Mines Act 1952.	A Mines manager is appointed to supervise Quarrying Operations.
2	Health and welfare measures for the persons employed shall be implemented.	Health and welfare measures for the employees are implemented and ensured.
3	Controlled blasting should be practiced, and blasting should be done only during day time. The mitigating measures for control of ground vibrations to arrest the fly rocks and boulders should be implemented.	All precautionary measures are adopted while blasting operations are carried out. I. No secondary blasting like Pop Shooting or Plaster Shooting are undertaken for breaking down large boulders, to avoid Air Blast and Fly Rocks. Only rock breakers will be used for breaking down bigger boulders. II. Additional precaution of controlled blasting with sand bags and wire mesh/blasting pads are used so that there are no fly rocks from the blast
4	Plantation shall be done which includes a green belt of adequate width around the Mining Lease area excluding the rocky area, along roads, overburden dumps and nonmineralized area by planting suitable native species in consultation with the local DFO/ Agriculture Department.	A green belt of a width of 7.5 mts has been made along the periphery of the Lease area by planting saplings in consultation with the local DFO/ Agriculture Department.
5.	The drains should be regularly desilted and maintained properly. Check dams and gully checks shall be constructed wherever required to arrest siltation. De siltation shall also be done every year before the onset of monsoon.	The drains will be constructed and maintained.
6	Fencing must be maintained properly all around the lease area.	The entire lease area is fenced and is well maintained.

7	The CSR should cover the felt needs of the locality with special emphasize for implementing ground water recharging techniques in and at the vicinity of the proposed site.	The CSR covers the needs of the locality with special emphasize for implementing ground water recharging techniques
8	Appropriate sign boards should be displayed	Signboards have been displayed. (Photos are attached as Annexure-1)
9	The blasting time must be displayed and strictly adhered to.	Blasting time is displayed and is strictly followed.
10	Dust suppression mechanism must be in place.	Water tankers with sprinklers are in use for dust suppression.
11	A separate small plot to be maintained in the premise to preserve rare and endemic species, if any, listed in the bio diversity assessment, etc.	No rare and endemic species is present in the lease area.
12	The PPV values must be less than 10 mm/sec.	PPV values are kept below 10 mm/sec.
13	The green belt shall be provided along the periphery.	Green belt of 7.5 mts width has been provided along the periphery of the lease area.
14	Where the height of the bench formed during earlier workings exceeds the maximum reach of the excavator engaged for work, such bench height shall be reduced from top to bottom.	Agreed. Bench heights are reduced from top to bottom.
15	Loose or hanging rock or mineral boulder on the side wall shall be dressed down before engaging persons for work at the bottom of the bench.	Benches are properly dressed by excavators and safety is ensured while employees are at the site.
16	Permanent boundary pillars should be fixed by the proponent before commencing quarrying.	Permanent boundary pillars are erected and maintained. (Photos are attached as Annexure-2)
17	No quarry blasting to be undertaken and sustained till warning time limit expires and/or when continuous 48 hours rainfall exceeds 8cms and blasting shall not be resumed until 24hours of rain free situation arises in the quarry locality based on the evaluation by the revenue officials.	Agreed.
18	All waste dumps and top soil dumps shall be properly stabilized using coir mats or bio regeneration. Proper drainage system shall be provided so that water is properly diverted away	Coir mats are used to cover waste dumps. Proper drainage systems are provided to divert the water away from the dump slopes.

	from the dumps slopes with no disturbance to the stability of the slopes.	
19	All dump slopes shall be sufficiently stabilized by using appropriate species mix of grass, creepers, shrubs and trees. This shall be done in consultation with the Forest department and local research institutes and experts I stabilization of mine dumps.	All dump slopes are stabilized by using mix of grass, creepers, shrubs and trees.
20	Garland drains of at least 2 mts width shall be provided all along 7.5 mts buffer zone to divert the water from entering the Quarry slopes. These drains shall be cleaned every year before the monsoon season	Garland drains of 2 mt width will be constructed.
21	The water from the garland drainage shall be directed to the silt settling ponds. The clarified overflow from the silt settling ponds shall be directed to a Rain Water Harvesting (RWH) pond before releasing the clarified water to the natural water course.	Only clear natural water is let out into the natural water course.
22	A retaining wall of stone rubble with wire (2 mt) shall be constructed at the bottom of the slope of the Quarry lease to arrest any likely mesh of sufficient width and strength (not less than roll of boulders during heavy rainfall.	Retaining wall will be constructed.

GENERAL CONDITIONS OF HEALTH

Sl.No.	Conditions	Status of compliance
1	First Aid kit provided in the work site. It shall be periodically maintained properly. Some labourers shall be trained on First Aid.	First Aid kits are provided for the labors in the work site and key personnel are trained to render first aid in case of emergencies.
2	Wholesome drinking water should be provided.	Drinking water is provided.
3	Premises should be maintained as wet to suppress the dust.	Site premises are well maintained as wet to suppress the dust.
4	Sanitary type of latrines and urinals should be provided.	Latrines and urinals are provided.
5.	Resting place to be provided for workers	Resting place is provided to workers.
6	'No Smoking' board should be exhibited according to COTPA act.	'No Smoking' board is exhibited at the site.
7	Work should not be done in night.	Work is done only during daytime.

8	Details of nearest hospital, shortest route to hospital and contact no. etc. should be available	Emergency contact numbers of Key persons, Hospitals, police station, etc. is prominently displayed.
9	Approach roads should be maintained properly	Approach roads are well maintained.

GENERAL CONDITIONS

Sl.No	Condition	Compliance Status
1	Rainwater harvesting facility should be installed as per prevailing provisions of KMBR/KPBR, unless otherwise specified.	Rainwater harvesting pond will be constructed.
2	Environment Monitoring Cell as agreed under the affidavit filed by the proponent should be formed and made functional.	Environmental Monitoring Cell has been formed and made functional.
3.	Suitable avenue trees should be planted along either side of the tarred road and open parking areas, if any, including approach roads and internal roads.	Avenue trees are planted along the either side of the tarred road.
4	Maximum Possible Solar Energy generation and utilization shall be ensured as an essential part of the Project.	Solar Energy generation and utilization shall be adopted.
5	Sprinklers shall be installed and used in the Project Site to contain dust emissions.	Water tankers with sprinklers are used to control dust emission.
6	Eco-restoration, including the Mine Closure Plan shall be done at the own cost of the Project Proponent.	Agreed.
7	At least 10 per cent of total excavated Pit area should be retained as water storage area and the remaining area should be reclaimed with stacked dumping and overburden and planted with indigenous plant species that are eco-friendly, if no other specific condition on reclamation of the Pit is stipulated in the EC.	Agreed.
8	Corporate Social Responsibility (CSR) agreed upon by the Proponent should be implemented.	CSR activities are implemented as agreed.
,	The Lease area will be fenced off with barbed wires to a minimum height of 4 ft around, before starting of Mining. All the boundary indicators (boards, stores,	Lease area is fenced off with barbed wires. Boundary pillars and sign boards have been erected and protected.
9	markings, etc.) shall be protected at all times and shall be conspicuous.	(Annexure 1 & 2)

10	Warning alarms indicating the time of Blasting (to be done at specific timings) has to be arranged as per stipulations of the Explosives department.	Necessary precautions are taken while blasting and is done at specific timings
11	Control measures on noise and vibrations prescribed by KSPCB should be implemented	Noise and vibrations are kept within KSPCB prescribed norms. I. Use of sharp drilling, delivery of compressed air at optimal pressure. II. Proper maintenance of compressor, drilling machine, jackhammers and tipper trucks. III. Regular monitoring of noise levels are being done within the core zone and the buffer zone of the mining lease area.
12	Quarrying activities should be limited to daytime as per KSPCB guidelines/specific conditions.	Quarrying activities limited to daytime.
13	Blasting should be done in a controlled manner as specified by the regulations of the Explosives department or any other agency.	Blasting is done in a controlled manner and is done technically as prescribed by the mining statutes. Only a small diameter drill holes of 33 diameter with 25mm cartridges slurry/ emulsion explosive are used for blasting, no large diameter holes are proposed for blasting. With optimum blast design, effective blasting techniques with delay detonators and low charges per delay, carte has been taken to limit the blast vibrations and the PPV value below 10mm per second.
14	A licensed person should supervise/control the Blasting Operations	Blasting supervision and control is done by a Mining Official having DGMS Certificate.
15	Access road to the quarry shall be tarred to contain dust emissions that may arise during transportation of materials.	Access road to the Quarry is tarred to control dust emissions.
16	Overburden materials should be managed within the site and used for reclamation of Mine Pit as per Mine closure Plan/specific conditions	Overburden material is used for road making and as a filler along the Green Belt for plantation purpose.
17	Height of Benches should not exceed 5 M and width should not be less than 5 M, if there is no mention in the Mining	Agreed.

	Plan/specific conditions	
18	Mats to reduce fly rock blast to a	Controlled blasting technique is
	maximum of 10 PPV should be provided	adopted. PPV is kept to a minimum.
19	Maximum depth of Mining from general ground level at site shall not exceed 10 m	Agreed.
20	No Mining operations should be carried out at places having a slope greater than 45°	Agreed.
21	Acoustic enclosures should have been provided to reduce sound amplifications in addition to the provisions of green belt and hollow bricks envelop for crushers so that the noise level is kept within prescribed standards given by CPCB/KSPCB.	Crusher unit is not installed within Mining Lease.
22	The workers on the site should be provided with the required protective equipment such as ear muffs helmet, etc.	Requisite Personal Protective equipments (PPE's) is provided to all employees at the site.
23	Garland drains with clarifiers to be provided in the lower slopes around the core area to channelize storm water.	Garland drains will be constructed and maintained.
24	The transportation of minerals should be done in covered trucks to contain dust emissions.	All trucks transporting material are covered by firmly tied tarpaulin
25	The proponent should plant trees at least 5 times the loss that has been occurred while clearing the land for the project.	Local species saplings have been procured from the Forest dept, Kannur and will be planted.
26	Disposal of spent oil from diesel engines should be as specified under relevant Rules/Regulations.	Spent oil is reused as a lubricant for drilling.
27	Explosives should be stored in magazines in isolated place specified and approved by the Explosive Department.	Explosives is stored in a Licensed Explosives Magazine, which is approved by PESO. (Copy of the Explosive license is attached as Annexure-3)
28	A minimum buffer distance of 100 M from the boundary of the quarry to the nearest dwelling unit or other structures, not being any facility for mining shall be provided. (Read as 50m)	No dwellings are situated within 50m from the boundary of the quarry.
29	100 M buffer distance should be maintained from forest boundaries.	Mining area is not located near any forest areas.
30	Consent from Kerala State Pollution Control Board under Water and Air Act(s) should be obtained before	Consent from KSPCB under Air and Water Act(s) is obtained. (copy of the consent is attached as Annexure-4)

	initiating mining activity.	
31	All other statutory clearances should be obtained, as applicable, by project proponents from the respective competitive authorities including that for blasting and storage of explosives.	All statutory clearances obtained. The DGMS permission is under process.
32	In the case of any change(s) in the scope of the Project, extent, quantity, process of mining technology involved or in any way affecting the environment parameters/impacts as assessed, based on which only the EC is issued, the project would require a fresh appraisal by this Authority, for which the proponent shall apply and get the approval of this Authority.	In case any change is required, a fresh appraisal will be submitted for obtaining Approval from the Authority.
33	The Authority reserves the right to add additional safeguard measures subsequently, if found necessary, and to take action including revoking of the Environmental Clearance under provisions of the Environment (Protection) Act,1986, to ensure effective implementation of the suggested safeguard measures in a time bound and satisfactory manner.	Agreed.

34	The stipulations by the Statutory Authorities under different Acts and Notifications should be complied with including the provisions of the Water (Prevention and control of Pollution) Act,1974, the Air (Prevention and control of Pollution) Act1981, the Environment (Protection) Act,1986, the Public Liability (Insurance) Act,1991 and EIA Notification,2006	Agreed.
35	The project proponent should advertise in at least 2 newspapers widely circulated in the region, one of which (both the advertisement and the newspaper) shall be in the vernacular language informing that the Project has been accorded Environment Clearance and the copies of the Clearance letters are available with the State Environment Impact Assessment Authority (SEIAA) office and may also be seen on the	Advertisements informing EC accordance to the Project is done in 2 newspapers and submitted in earlier reports.

	website of the Authority at www.seiaakerala.org The advertisement should be made within 10 days from the date of receipt of the clearance letter and a copy of the same signed in all the pages should be forwarded to the Office of this Authority as confirmation	
.36	A copy of the clearance letter shall be sent by the proponent to the concerned Gram Panchayat/District Panchayat/Municipality/Corporation/Urban local Body and also to the Local NGO, if any from whom suggestions/representations, if any were received while processing the proposal. The Environmental Clearance shall also be put on the website of the company by the proponent.	A copy of the Clearance is submitted to the Pattiam Gram Panchayat on.
37	The proponent shall submit half yearly reports on the status of compliance of the stipulated EC conditions including results of monitored data (both in hard copies as well as by e-mail) and upload the status of compliance of the stipulated EC conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the respective Regional office of the MOEF, Govt. of India and also to the State Environment Impact Assessment Authority (SEIAA) office	Half yearly reports are submitted as stipulated.
38	The details of Environment Clearance should be prominently displayed in a metallic board of 3 ft x 3 ft with green background and yellow letters of Times Roman font of size not less than 40. Sign board with extent of Lease area and boundaries shall be depicted at the entrance of the quarry, visible to the public	Details of Environmental Clearances are prominently displayed at the entrance to the Mine. (Photo of the sign boards are attached as Annexure-1)
39	The proponent should provide notarized affidavit (indicating the number and date of Environmental Clearance proceedings) that all the conditions stipulated in the EC shall be scrupulously followed.	Already provided notarized affidavit.
40	No change in mining technology and scope of working should be made without prior approval of the SEIAA. No further expansion or modifications in the mine shall be carried	Prior approval from the SEIAA will be sought in case of change of mining technology.

	out without prior approval of the SEIAA, as applicable.	
41	The Project proponent shall ensure that no natural water course and/or water resources shall be obstructed due to any mining operations. Necessary safeguard measures to protect the first order streams, if any, originating from the mine lease shall be taken.	No natural water course is obstructed. Necessary safeguard measures will be taken to protect first order streams if originating from the mining lease in the future.
42	Monitoring of Ambient Air Quality to be carried out based on the Notification 2009, as amended from time to time by the Central Pollution Control Board. Water sprinkling should be increased at places loading and unloading points & transfer point to reduce fugitive emissions.	Monitoring of Ambient Air Quality are carried out. Water sprinkling are done at places loading and unloading points & transfer point to reduce fugitive emissions. (Monitoring Photos and Monitoring Reports are attached as Annexure 5 & 6)
43	The top soil, if any, shall be temporarily be stored at earmarked site(s) only for the topsoil shall be used for land reclamation and plantation. The Over burden (OB) generated during the mining operations shall be stacked at earmarked dump site(s) only. The maximum height of the dumps shall not exceed 8 m and the width 20 m and overall slope of the dumps shall be maintained to 45°. The OB dumps should be scientifically vegetated with suitable native species to prevent erosion and surface run off. In critical areas, use of geo-textiles shall be undertaken for stabilization of the dump. The entire excavated area should continue until the vegetation becomes self-sustaining	Available top soil will be used at the Green belt for plantation. OB generated is used for plantation purposes along the Green/Safety zone.
44	Catch drains and siltation ponds of appropriate size shall be constructed around the mine working, mineral and OB dumps to prevent run off of water and flow of sediments directly into the river and other water bodies. The water so collected should be utilized for watering the mine area, roads, green belt development, etc. The drains shall be regularly de silted particularly after monsoons and maintained properly	Catch drains will be made along the periphery of the mining lease.
45	Effective safeguard measures such as regular water sprinkling shall be carried out in critical areas prone to air pollution and having high levels of PM10 and PM2.5 such as haul road, loading and unloading points	Regular water sprinkling is done on haul roads, loading and unloading points with water tankers.

	and transfer points-it shall be ensured that	
	the Ambient Air Quality parameters conform to the norms prescribed by the Central Pollution Control Board in this regard.	
46	Fugitive dust emissions from all sources should be controlled regularly. Water spraying arrangements on haul roads, loading and unloading and transfer points should be provided and properly maintained.	Fugitive dust emissions are controlled with water spraying arrangements on haul roads, loading and unloading and transfer points.
47	Measures should be taken for control of noise levels below 85 dB(A) in the work environment.	Adequate measures for noise control is adopted.
48	A separate environmental management cell with suitable qualified personnel should be set up under the control of a senior executive, who will report directly to the head of the Organization.	An Environment Management Cell is set up under the control of the Mines Manager.
49	The funds earmarked for environment protection measures and CSR activate should be kept in a separate account and should not be diverted for other purpose. Year wise expenditure should be reported to the State Environment Impact Assessment Authority (SEIAA) office.	The funds earmarked for environment protection measures and CSR activities are kept in a separate account and is not diverted for any other purpose.
50	The Regional Office of MOEF and CC located in Bangalore shall monitor compliance of the stipulated conditions. The Project authorities should extend full cooperation to the Officer(s) if the Regional Office by furnishing the requisite data/information/monitoring reports.	We will extend full cooperation to any officer(s) from the Regional Office during his/their visit. All available data will be provided.
51	Any appeal against the Environment Clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010	Agreed.
52	Concealing the factual data or submission of false/fabricated data and failure to comply with any of the conditions mentioned above may result in withdrawal of this clearance and attract action under provisions of the Environment (Protection) Act, 1986.	Factual and true data will be submitted.
53	The SEIAA may revoke or suspend the order for non-implementation of any of the specific or this implementation of any of the above conditions is not satisfactory. The SEIAA reserves the right to alter/modify the	Agreed.

	above conditions or stipulate any further condition in the interest of the environment protection	
54	The above conditions shall prevail not withstanding anything to the contrary, inconsistent or simplified, contained in any other permit, license on consent given by any other authority for the same project.	Agreed.
55	The order is valid for a period of 5 years of the expiry date of Mine lease period issued by the Government of Kerala, whichever is earlier	Agreed.
56	The Environment Clearance will be subject to the final order of the courts in any pending litigation related to the land or the project, in any court of law.	Agreed.
57	The Mining operations shall be restricted to above ground water table and it should not intersect ground water table.	Mining operations will be restricted above the ground water table and due care will be taken so as not to intersect ground water.
58	All vehicles used for transportation and within the mines shall have 'PUC' certificate from authorized pollution checking center. Washing of all vehicles shall be inside the Lease area	Will ensure that all transportation vehicles have PUC issued by an authorized Pollution checking center.
59	Project proponent should obtain necessary prior permission of the competent authorities for drawl of necessary quantity of surface and ground water for the project.	Agreed.
60	Regular monitoring of flow rates and water quality upstream and downstream of the springs and perennial nallahs flowing in and around the mine lease area shall be carried out and reported in the six-monthly reports	No perennial nallah flows through the lease or exist around the Mine Lease.
61	Occupational health surveillance program of the workers should be undertaken periodically to observe any contractions due to exposure to dust and take corrective measures, if needed.	Occupational health surveillance will be undertaken.

For 'Granite Building Stone of Mr. C.G. George'

(Mr. C.G. George) Owner

23.07.2020



Sign Boards









Boundary Pillars and Fencing







GOVERNMENT OF INDIA MINISTRY OF COMMERCE & INDUSTRY PETROLEUM AND EXPLOSIVES SAFETY ORGANISATION(PESO)

(Formerly Department of Explosives) Kendriya Bhavan, Block C-2, 3rd Floor

CSEZ PO Kakkanad Dist. Ernakulam Ernakulam 682037 Tele: 2427286 Fax: 2427276

Email: dycceernakulam@explosives.gov.in

No.: E/SC/KL/22/746(E32353)

Dated: 13/01/2015

10. Shri C.G.George. Chipath House,Kuthuparamba post, TownVillage - Kuthuparambu Mistrict-KANNUR, State-Kerala, Pincode - 670643

Subject:

Possession for Use of of Explosives from magazine situated at Survey No(s)::88/1, Kolavallur, Thalassery Tk., Dist. KANNUR, Kerala -Licence No.: E/SC/KL/22/746(E32353) granted in Form LE-3 of Explosives Rules, 2008 - Amendment of Quantity of Explosives/Monthly Purchase Limit.

Sir(s).

Please refer to your letter No. nil dated 11/12/2014 on the subject cited above.

The Licence No.: E/SC/KL/22/746(E32353) is forwarded herewith duly amended in respect of followings;
THIS IS FOR ADDITIONAL QUARRY AT SY.No.73/81/1-2, PATTIAM VILLAGE, THALASSERY TALUK, KANNUR. VALID PERMISSIONS, AS APPLICABLE, FROM THE STATE GOVERNMENT AGENCIES SHALL BE IN POSSESSION...

The licence capacity at any one time shall not exceed the kinds and quantities mentioned below;

No	Explosive(s)	Class	Div	Sub Div	Capacity	Unit
1	Nitrate Mixture	2	0	0	150	Kg.
		6	1	0	2000	Mtrs
2	Safety Fuse	0	1	· ·		
2	Electric Detonators	6	3	0	2500	Nos.
3			2	0	5000	Nos.
4	Ordinary Detonator	6	3	0	3000	11001

Quantity of explosives to be purchased in a calendar month[applicable for licence under article 3(b) and (c)]: 20 times as above.

This Licence shall remain valid till 31st day of March 2019.

An amount of Rs. 2640/- balance is in your credit, which may be utilized for future transaction by quoting this reference.

For further renewal of licence, please follow the procedure under Rule 112 of Explosives Rules, 2008. Receipt of this letter may please be acknowledged.

Enclosures :

Copy Forwarded to:

1. District Magistrate, KANNUR, Kerala with reference to his Noc No: D4.5631/2005 Dated: 18/10/2005.

2. Superintendent of Police, KANNUR, Kerala

Deputy Chief Controller of Explosives Ernakulam

[For more information regarding status, fees and other details, please visit our web site http://peso.gov.in]



भारत सरकार | Government of India

याणिज्य और उद्योग मंत्राल्य | Ministry of Commerce & Industry पेट्रोलियम तथा विस्फोटक सुरक्षा संगठन (पेसी) | Petroleum & Explosives Safety Organisation (PESO)

पूर्व नाम विस्फोटक विभाग | Formerly- Department of Explosives केन्द्रीय अयम, ब्लाक सी-2, तीसरी मंजिल | Kendriya Bhavan, Block C-2, 3rd Floor CSEZ पी.ओ.कक्कानाइ कोच्यो | CSEZ PO Kakkanad Dist. Ernakulam Ernakulam 682037

फोल (Phone):- 2427286 | फैक्स (Fax):- 2427276 ई-मेल Email: dycceernakulam@explosives.gov.in

संख्या (No.): E/SC/KL/22/746(E32353)

दिनांक (Date): 07/02/2019

नेवा में | To,

Shri C.G.George,

Chritath House, Kuthuparamba post, Town/Village - Kuthuparambu District-KANNUR, State-Kerala, Pincode - 670643

E 8 FER 2019

विषय :

Subject:

Survey No(s),88/1, ग्राम Kolavallur,Thalassery Tk., जिला KANNUR, राज्य Kerala में विस्फोटक के मैगजीन में उपयोग के लिए कब्जा हेतु विस्फोटक नियम, 2008 के अंतर्गत LE-3 में जारी अनुजिस सं E/SC/KL/22/746(E32353) के नवीनीकरण संदर्भ में।

Possession for Use of of Explosives from magazine situated at Survey No(s):88/1, Kolavallur, Thalassery Tk., Dist. KANNUR, Kerala -Licence No.: E/SC/KL/22/746(E32353) granted in Form LE-3 of Explosives Rules, 2008 - Renewal regarding

महोदय | Sir.

भापका उपर्युक्त विषय पर पत्र संख्या Nil दिनांक 30/01/2019 का संदर्भ ग्रहण करें। विस्फोटक नियम, 2008 के अंतर्गत प्ररूप LE-3 में जारी अनुजिस दिनांक 31/3/2024 तक नवीनीकृत कर इस पत्र के साथ भेजी जा रही है।

Reference to your letter No.: Nil dated: 30/01/2019, the subject licence duly renewed upto 31/3/2024 and issued in Form LE-3 of Explosives Rules, 2008 is

orwarded herewith.

अनुज्ञति के आगामी नवीकरण हेतु कृपया निम्नलिखित दस्तावेज दिनांक 31/03/2024 से पहले **इस कार्यां**लय को भेजे जाएं. For further renewal of licence, please submit the following documents so as to reach this office on or before 31/3/2024.

 प्ररूप आरई-। में विधिवत पूर्ण एवं हस्ताक्षरित आवेदन। Application in Form RE-1 duly filled in and signed.

 एक से पाँच वर्ष के अनुज्ञित शुल्क का बैंक ड्राफ्ट। बैंक ड्राफ्ट किसी भी राष्ट्रीयकृत बैंक के नाम आहरित, संयुक्त मुख्य विस्फोटक नियंत्रक, चेल्नई के पक्ष में चेन्नई में देय हों। Licence fees for one to five years in the form of demand draft drawn on any Nationalized Bank in favour of Jt. Chief Controller of Explosives,

Chennai payable at Chennai. अनुमोदित प्लान के साथ मूल अनुजिता।

Original licence with approved plan.

 कृपया इस संबंध में विस्फोटक नियम, 2008 के नियम 112 का भी संदर्भ ग्रहण करें। In this connection, please also refer to Rule 112 of Explosives Rules, 2008

 विस्फोटकों के क्रय हेतु आरई-11 में मांगपत्र (इंडेंट)आपूर्तिकर्ता को दिया जाए और उसी की एक प्रति इस कार्यालय को भेजी जाएं (आतिशबाजी गोदाम के लिए लागू नहीं)।

Indent for purchase of explosives shall be placed in RE-11 with the supplier and copy of the same shall be sent to this office. (Not applicable for fireworks store house)

• कृपया विरूफोटकों की त्रैमासीक विवरणी हर तिमाही के अंत में आरई-7 में प्रस्तुत की जाएं । विवरणी इस कार्यालय के कार्यालय में आगामी तिमाही के 10 तारीख से पहले पहुंच जानी चाहिए (आतिशयाजी गोदाम के लिए लागू नहीं) | Please submit quarterly returns of explosives in RE-7 at the end of every quarter so as to reach this office by 10th of the succeeding quarter. (Not applicable for fireworks store house)

 सभी ब्लास्टिंग आपरेशन एक सक्षम द्वारा की जाएगी जो उपरोक्त नियमों के तहत एक वैध शोंट फायर प्रमाणपत्र धारक हो। हालांकि, खात अधिनियम 1952 के अधीन आने वाले खानों में ब्लास्टिंग आपरेशन करने वाले ब्लास्टर की योग्यता उसी अधिनियम से निर्धारित हो। All blasting operations shall be carried out by a competent person holding a valid shot firer's permit granted under above rules. However, blasting operations in mines coming under the purview of the Mines Act 1952, the blaster shall have qualifications prescribed in the regulations framed under the said Act.

आपके खाते में रुपए 1840/- की राशि शेष हैं जो इस संदर्भ को उद्धत करते हुए भविष्य के संव्यवहार में समायोजित की जा सकती है । An amount of Rs. 1840/- balance is in your credit, which may be utilized for future transaction by quoting this reference.

भवदीय | Your's faithfully

(आर.वेणुगोपाल | Dr. R.Venugopal)

उप मुख्य विस्फोटक नियंत्रक | Deputy Chief Controller of Explosives

कोच्ची | Emakulanı विस्फोटक नियंत्रक

Deputy Chief Controller of Explosives

प्रतिलिपि पेषित | Copy Forwarded to: 1. जिला मजिस्ट्रेट (District Magistrate), KANNUR (Kerala)-सूचना के लिए (for information.) एरणाकुलम Ernakulam

उप मुख्य विस्फोटक नियंत्रक | Deputy Chief Controller of Explosives

कोच्ची | Ernakulam



KERALA STATE POLLUTION CONTROL BOARD

FILE NO. :PCB/KNR/ICO/OC/11/2018

Date of issue :2018-01-10

CONSENT VARIATION ORDER

Consent No: R15KANCTOA455875

Ref: 1. Consent No:R15KANCTOA455875 dated 21/05/2015

The 'Integrated Consent to Operate' issued as per reference above to M/s Quarry Owned By CG George, Pattiam, Kuttiyeri poyil, Kannur is hereby modified & issued to M/s Quarry Owned By CG George, Pattiam, Kuttiyeri poyil, Kannur The consent(s)/ variation order(s) cited under reference are integral part of this consent variation order and this order is subject to the conditions stipulated therein and the following modifications/additions

I. GENERAL

S.No.	Items	Description			
1	1.1 VALIDITY	31/10/2022			
2	1.5 SURVEY NUMBER	81/1,81/2			
3	1.13 CAPITAL INVESTMENT	19.00 LAKHS			
4	1.12 ANNUAL FEE	3670/-			
5	1.18 PRODUCTS	Granite quarrying of 0.7682 Ha in RS NO.81/1,81/2 of Pattiam Village of Thalassery Thaluk.			
6	1.12 FEE REMITTED	18350/-			

II. CONDITIONS

- 2.2 Application for renewal of consent shall be submitted before 30/07/2022.
- 2.5 Deleted.
- 3.2 Deleted
- 3.3 Deleted
- 4.1 Permanent fence made of wire mesh shall be provided and maintained along the boundary of the approved quarry area.
- 4.2 Deleted.

- 4.3 Deleted
- 4.4 Deleted.
- 4.5 There shall be a minimum distance of 50 m from the boundary of the quarry to the nearest residence, places of worship, railway line, bridge, water body, public building and public road having vehicular traffic.
- 4.8 Location of quarry shall be as per the drawing attached. No change or alteration to the above shall be made
- 4.11 Deleted

All other conditions of the Integrated Consent to Operate issued as per reference above remain unchanged.

DATE :10/01/2018

SIGNATURE & SEAL OF ISSUING AUTHORITY ENVIRONMENTAL ENGINEER



To

CG George Chitteth House, Kuthuparamba, Kannur

- 1. This digitally signed document is legally valid as per the Information Technology Act 2000
- 2. For verifying this document please go to krocmms.nic.in and search using date of issue/name of the unit/Application Number in "Consent Granted Applications" link in the home page of the Board's Online Consent Management and Monitoring System.



പാട്യം ഗ്രാമ പഞ്ചായത്ത്

mo 02/2019-20

1994 ലെ കേരളാ പഞ്ചായത്ത് രാജ് ആക്ട് (1994 ലെ 13) 232, 233, 234, 254 എന്നീ വകുപ്പുകൾ പ്രകാരവും അതേ തുടർന്നുള്ള ചട്ടങ്ങളും അനുസരിച്ചു കൊടുത്തത്

ഫാക്ടറികള് , വ്യവസായങ്ങള് , സംരംഭങ്ങള് , മറ്റു സേവനങ്ങൾ എന്നിവയ്ക്കായി നൽകുന്ന ലൈസന്ദസ്

ലൈസന്റസുടമസ്ഥന്റെ പേരും സി.ജി ജോർജ്ജ് ചിറ്റേത്ത് ഹൌസ്, കൂത്തുപറമ്പ് മ്രൽവിലാസവും എന്താവശ്യത്തിന് ലൈസൻസ് |അനുവദിച്ചു എന്ന് കരിങ്കൽ ക്വാറി കെട്ടിടത്തിന്റെ നന്പരും സർവ്വേ നം 81/1,81/2 സ്ഥാനവും ലൈസൻസിന്റെ കാലാവധി 2019-2024 ലൈസൻസ് ഫീസ് ചാലാവധി തീരുന്ന മുറയ്ക്ക് ആയത് പൂതുക്കി നൽകിയ ലൈലൻസിന് 31-03-2024 വരെ സാധ്വതയാണ്ടാകാകയാഒരാ Rs. 50000 മറ്റു വകുപ്പുകളന്ത നന്നും ലഭ്യമാക്കിയ സാക്ഷ്യപത്രങ്ങളുടെ കാലാവധി തീരുന്ന മുറയ്ക്ക് ആയത് പൂതുക്കി നൽകിയാൽ മാത്രമേ റിമാർക്ക്സ്

സ്ഥലം: പത്തായക്കുന്ന് തീയതി: 03-04-2019

PATHAYAKUT

പി. ഒ. പത്തായക്കുന്ന് ഫോൺ:9496049134

Licence Generator ver 5.0 developed by Prakash Vorkady











5

Report No

GLOBAL Environment & Mining Services

Consulting Engineers, Mine designers, Geologist & Surveyors)

3 M Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist.., Bellary (Kamataka)

: +91 8394 229433 & 295018 -Ph esmail gems hpt@yahoo.com.

Website www.globalmining.in

> GEMS-LD/TF/11/01 Date: 20.02.2020

Analysis Report of Ambient Air Quality Monitoring

Granite Building Stone Quarry of

Mr. C. G. George.

Name of the Customer/Address : Extent: 0.7682 Ha. (1.8982 Acres)

Sv. Nos: 156, Patiom Village, Thalassery Taluk,

Kannur District, Kerala State.

Sample Description : Ambient Air Quality Monitoring

3 : GLOBAL Environment & Mining Services Sample Collected By 4

: 24 Hour of Sampling

Duration of the Monitoring Location of Monitoring : (A1) Core zone

: ULR-TC5323200000000065F

Result

Si	Date		Pa	Parameters in μg/m	n ³	
No.		PM_{10}	PM _{2.5}	SO ₂	NO ₂	Lead in PM
1	18.02.2020	56.1	23.6	13.4	14.8	BDL
NAA	AQ Standards 2009	100	60	80	80	1.0

PM10 - IS 5182 (Part 23): 2006 (RA 2017)

PM2.5 - USEPA 2001

502 - IS 5182 (Part 2): 2001 (RA 2017) BDL (<3.0) NO2 - IS 5182 (Part 6): 2006 (RA 2017) BDL ((<5.0)

- IS 5182 (Part 22): 2004 (RA 2014) Lead

BDL. - Below Detectable Limit.

Analyzed By J.M. Thippeswamy Chemist

K. Ramakriskoa Red Technical Mar

- The result fixed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days. Minerals 3 Months. Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise.
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing

Total liability of our laboratory is limited to the Invoice amount. Any dispute arising our of this report is subject to Hosapete jurisdiction only

Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory Recognized by Government of Karnataka, Mahamahtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3 nl Main Road Basaveswara Badavane

HOSPET - 583201, Dist .. Bellary (Karnataka) : +91 8394 229433 & 295018

: gems hot@valroe.com. e-mail Website www.globalmining.in

> GEMS-LD/TF/11/01 Date: 20.02.2020

Analysis Report of Ambient Air Quality Monitoring

Granite Building Stone Ouarry of

Mr. C. G. George.

Name of the Customer/Address

: Extent: 0.7682 Ha. (1.8982 Acres)

Sv. Nos: 156, Patiom Village, Thalassery Talu

Kannur District, Kerala State.

2 Sample Description

: Ambient Air Quality Monitoring : GLOBAL Environment & Mining Services

3 Sample Collected By 4 Duration of the Monitoring

: 24 Hour of Sampling

5 Location of Monitoring

: (A2) Buffer Zone

Report No

: ULR-TC532320000000066F

Result

Si	Date		Pa	rameters in μg/r	n³	
No.		PM_{10}	PM _{2.5}	SO ₂	NO ₂	Lead in PM
1	17.02.2020	39.1	19.5	12.1	11.4	BDL
NAA	AQ Standards 2009	100	60	80	80	1.0

PM10 - IS 5182 (Part 23): 2006 (RA 2017)

PM2.5 - USEPA 2001

SOZ - IS 5182 (Part 2): 2001 (RA 2017) BDL (<3.0) - IS 5182 (Part 6): 2006 (RA 2017) BDL ((<5.0) NO2

Lead - IS 5182 (Part 22): 2004 (RA 2014)

RDI. - Below Detectable Limit.

Analyzed By J.M. Thippeswamy Chemist

K. Ramakfishna Post Technica Manage

Note:

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Fitter papers & Thimbles 7 Days and fLC samples from the date of Issue of Month test certificate unless otherwise
- This report is not to be regraduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing Total Hability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory

Recognized by Government of Karnataka, Malsarashtra, Goz for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3 ^{nl} Main Road, Basayeswara Badayane

HOSPET - 583201 Dist. Bellary (Karnataka) +91 8394 229433 & 295018 Ph e-mail gems hpt@vahoo.com. www.globalmining.in

> GEMS-LD/TF/11/01 Date: 20.02.2020

TEST REPORT OF AMBIENT NOISE LEVEL MONITORING

Website

Granite Building Stone Quarry of

Mr. C. G. George,

Name of the Customer/Address : Extent: 0.7682 Ha, (1.8982 Acres)

Sv. Nos: 156, Patiom Village, Thalassery Taluk,

Kannur District, Kerala State.

Sample Description

3 Sample Collected By

4 Particulars of Sample Collected

5 Duration of the Monitoring

Date of Analysis Completion

Report No

Ambient Noise Level monitoring

GLOBAL Environment & Mining Services

Noise Level Meter (Equinox-107)

: 24 Hours Sampling : 19.02.2020

: ULR-TC5323200000000067F

Result

Date	1	16.02.2020	18.02.202	20	
Name of the Location		Core Zone	Buffer zo	ne	
Time (hrs)		N1	N2		
6.00		35.1	42.4		
7.00		37.4	43.6		
8.00		40.1	47.1		
9.00		50.2	45.1		
10.00		52.7	48.2		
11.00		51.6	50.0		
12.00		50.5	51.2		
13.00		54.3	52.3		
14.00		55.7	53.3		
15.00		56.6	54.1	<-	
16.00		50.3	50.3		
17.00		51.2	45.3	-	
18.00		50.4	47.2		
- 19.00		48.7	48.8		
20.00		47.9	49.5		
21.00		39.0	46.2		
22.00		36.0	45.4		
23,00		39.6	38.4		
00.00		40.0	38.0		
01.00		35.2	39.0		
02.00		37.0	37.3		
03.00		36.2	38.5		
04.00		36.6	39.6		
05.00		34.8	36.7		

- Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognized by Government of Kamataka, Maharashtra, Goa for DGPS survey

Note:

- The result listed refers only to the reside samples & applicable parameters. Enforcement of products is aeither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month text certificate unless otherwise
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & about not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only





(Consulting Engineers, Mine designers, Geologist & Surveyors)

3 nl Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Kamataka) -

-91 8394 229433 & 295018

o-mail gems hpt@vahoo.eom. Website : www.globalmining.in

	- 8	ULR-TC532320000000067F				
L max	56.6	54.1				
L min	34.8	36.7				
Ld	51.5	49.7				
Ln	37.5	41.3				
Ldn	50.4	50.5				

Ph

	9254000-9000-82400000	Limit in dB(A) Leq		
Area Code	Category of Area	Day Time	Nighttime	
A	Industrial Area	75	* 70	
В	Commercial Area	65	55	
C	Residential Area	55	45	
D	Silence Area	50	40	

Day time shall mean from 6:00 am and 10:00 pm

Night time shall mean from in between 10.00 pm and 5.00 am

Silence zone is an area comprising not less than 100 meters around hospitals, educational institutions, courts, religious places or any other area which is declared as such by the competent authority

Mixed categories of areas may be declared as one of the four above mentioned categories by the competent authority

*dB(A) Leg denotes the time weighted average of the level of sound in decibels on scale A which relatable to human being

A "decibel" is a unit in which noise is measured

"A", in dB(A) Leg, denotes the frequency weighting in the measurement of noise and corresponds to frequency response characteristics of the human ear.

Leg: It is energy mean of the noise level over a specified period.



- Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognized by Government of Kamataka, Maharashtra, Gos for DGPS survey

Note:

Note

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise.
- This (eport is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3 nd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist.., Bellary (Kamataka) : +91 8394 229433 & 295018 e-mail gems hpt@yahoo.com,

Website : www.globalmining.in

EMS-LD/TF/11/01 Date: 20.02.2020

ANALYSIS REPORT OF WATER QUALITY DATA

Granite Building Stone Ouarry of

Shri. A.B.Prasad.

Extent: 0.9834 Ha. (2.4299 Acres)

: Re-Sy Block No: 14,Re-Sy.Nos: 197/5,197/5-

Kanjirappally Village, kanjirappally Taluk,

Kottavam District, Kerala State,

: GLOBAL Environment & Mining Services

: Grab Sample

: 15.02.2020

: 18.02.2020

Date of sample Received Date of sample Analyzed : 20.02.2020 Report Number : ULR-TC5323200000000068F

Name of the Customer/Address

Sample Collected By

Date of sample collection

Sampling Method

Result

Sl.	Parameters	Unit	Result	Test Protocol	Requirement/Limit IS: 10500: 2012	
					Acceptable	Permissible
1	pH		7.1	APEIA 22th Edition 2012 4500 B (Pg No. 4-92 to 4-96)	6.5	8.5
2	Colour*	Hazen	<5	IS: 3025 (PART 14)- 1984, RA- 2012 Platinum cobalt Method	5	15
3.	Taste*	9	Λg	IS 3025 Part 8 1984	Ag	Ag
4.	Odour*		Ag	1S; 3025 (Part 5) 4983, Ra-2012, True Odour	Ag	Ag
5.	Turbidity	NTU	0.36	APHA 22 nd Edition 2012 2130 B (Pg No. 2-14)	1	-5
6.	Conductivity	μS/cm	191	APHA 22 nd Edition 2012 2510 B (Pg No. 2-54)	*	50
7.	Total Dissolved Solids	mg/L	-178	APHA 22 ^{tol} Edition 2012 2540 B (Pg No. 2-65)	500	2000
8.	Total Alkalinity as CaCO ₁	mg/L	51 .	APHA 22th Edition 2320 B (Pg No. 2-35)	200	600
9	Total Hardness as CaCO ₃	mg/L	110	APHA 22 nd Edition 2012 2340 C (Pg No. 2-46)	200	600
10.	Calcium as Ca	mg/L	20	APHA 22 nd Edition 2012 3500 Ca B (Pg No. 3-84)	75	200
11.	Magnesium as Mg	mg/L	63	APHA 22 ^{nt} Edition 2012 3500 B-Mg By Calculation	30	100
12.	Chloride as CI	mg/L	21.2	APHA 22 rd Edition 2012 4500 C1 (Pg No. 4-72)	250	1000
13.	Sulphate as SO ₁	mg/L	91	APHA 22 rd Edition 2012 4500 SO42 – E (Pg No. 4-190)	200	400
14.	Nitrates as NO ₃	mg/L	3.10	APHA 23 nd Edition - 4500 NO ₃ - E (Pg No. 4-131 to 4-132)	45	NR
14.	Nitrate Nitrogen as NO:	mg/L	14	APHA 22 st Edition 2012 4500 NO3 E (Pg No. 4-125 to 4-127)	45	No relaxation

- Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory Recognized by Government of Kamanaka, Maharishtra, Gox for DGPS survey

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is acitter inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Mondis, Filter papers & Thimbles 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing
- Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only





(Consulting Engineers, Mina designers, Goologist & Surveyors) 3 nd Main Road, Basaveswara Badavane, HOSPET - 583201, Dist..., Bellary (Karnataka)

+91 8394 229433 & 295018 e-mail : gems_hpt@yahoo.com, Website : www.globalmining.in

	-					ULR-TC5323200000000068F
15.	Fluoride as F	mg/L	0.81	APHA 23 nd Edition 2017 4500 F-D (Pg No. 4-90 to 4-91)	1.0	1.5
16.	Iron as Fe	mg/L	0.41	APHA 23 rd Edition = 3500 Fe-B (Pg No. 3-80 to 3-82)	0.3	NR
17.	Sodium as Na	mg/L	7.14	APHA 23 ^{ad} Edition 2017 Na 3500 B (Pg No. 3-99 to 3-100)	18	
18.	Potassium as K	mg/L	0.80	APHA 23 nd Edition 3500 K B (Pg No. 3-89 to 3-90)	-	(4)
19.	BOD 3 days at 27° C	mg/L	NIL	(S.3025 (P.44) - 1993 , RA-2014,	-	
20.	COD as O2	mg/L	NIL	APHA 23 rd Edition 5220 C (Pg No. 5-18 to 5-19)	-	*
21.	Oil & Grease	mg/L	NIL.	APHA 23 rd Edition 5520 B (Pg No.5-41 to 5-42)	0.5	NR
22.	Cadmium as Cd*	mg/L	< 0.001	APHA 23 ^{R3} Edition-3111 –B. (Pg No 3-20 to 3-21)	0.003	NR
23.	Copper as Cu	mg/L	< 0.001	APHA-23 ⁸⁰ Edition 3111-B (Pg No.3-20 to 3-21)	0.02	1.5
24.	Nickel as Ni	mg/L	<0.001	APHA-23 ^{RO} Edition-3111 -B (Pg No. 3-20 to 3-21)	0.02	NR
25.	Zinc as Zn	mg/L	<0.1	APHA-23 RD Edition-3111-B (Pg No. 3-20 to 3-21)	.5	15
26,	Salinity*	PPT	NIL	APHA-23 RD Edition-3111-B (Pg No. 3-20 to 3-21)	-	-
27.	Total Phosphorous	mg/L	< 0.01	APHA-23 RD Edition 4500-D (Pg No. 4-154)		
28.	Total Coliforms*	MPN/ 100ml	Ab	APHA 22 rd Edition 9222 B (Pg No.9-78)	**	
29.	Feacal Coliforms	MPN/ 100ml	Ab	APHA 22 rd Edition 9222 D (Pg No.9-85)		
30.	Phyto Plankton*	Unit/L	Ab	APHA 23 rd Edition 10200 F (Fg No.10-17)		

Note: BDL Below Detectable Limit

Ag: Agreeable NR: No Relaxation RA: reaffirmed Ab: Absent

End of report

Analyzed By Chemist



- Approved by NABL & Recognized by Ministry of Environment, Forest and Climate Change for Laboratory Recognized by Government of Karnataka, Muharashtra, Goa for DGPS survey

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither infured nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Fifter papers & Thimbies 7 Days and ILC samples from the date of issue of Month test certificate unless otherwise specified.
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

 Total fiability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only